

*a measurable difference...*

## Foam Resilience Tester

### Model: F0020

This test aims to determine the resilience of flexible cellular polyurethane. A steel ball is dropped vertically on to a test piece and the rebound height measured and expressed as a percentage of the height dropped.

### Applications:

- Flexible cellular polyurethane

### Features:

- Transparent rigid tube
- 5% mark complete circle
- 1% mark 120° arc

### Standards:

- AS 2282.11
- ASTM D3574 - Test H
- ISO 4651:1988
- ISO 8307
- JIS K 6400
- BS EN ISO 4651
- DIN EN ISO 4651
- EN ISO 4651
- BS EN ISO 8307
- DIN EN ISO 8307
- EN ISO 8307

### Connections:

- **Electrical:** 220/240 VAC @ 50 HZ or 110 VAC @ 60 HZ

*(please specify when ordering)*

### Dimensions:

- **H:** 600mm
- **W:** 535mm
- **D:** 535mm
- **Weight:** 7kg



10-11 Colorado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885

Fax: +61 3 9708 6770

Website: [www.idminstruments.com.au](http://www.idminstruments.com.au)

Email: [idm@idminstruments.com.au](mailto:idm@idminstruments.com.au)

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments reserves the right to make alterations to its product range from time to time.