

a measurable difference...



Roller Shear Machine

Model: R0010

The Roller Shear Machine is used to determine the resistance to compression fatigue of flexible cellular polyurethane using dynamic roller compression test. The Roller Shear Machine fatigues a specimen dynamically with a constant force deflecting the material both vertically and laterally. It has been used for many years in the foam industry to determine the percentage loss in thickness.

Application:

- Flexible Cellular Polyurethane

Features:

- Base Platen 500mm x 500mm x 10mm
- Stainless Roller 500mm long, 76.0mm dia.
- Roller Offset 15°
- Roller loading 130N (adjustable)
- Cycle frequency 0.5Hz
- Stroke length 300mm
- Cycle Counter
- Floor standing machine
- Safety Guard

Standards:

- ASTM D1564
- AS 2282.12 Clause 3.3, Method B
- ASTM D3574

Options:

- N/A

Connections:

- **Electrical:** 220/240 VAC @ 50 HZ or
110 VAC @ 60 HZ

(please specify when ordering)

Dimensions:

- **H:** 1,423mm
- **W:** 1,600mm
- **D:** 800mm
- **Weight:** 200kg



10-11 Colorado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885

Fax: +61 3 9708 6770

Website: www.idminstruments.com.au

Email: idm@idminstruments.com.au

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments reserves the right to make alterations to its product range from time to time.

Copyright © 2006 IDM Instruments Pty Ltd. All Rights Reserved.